



MARINE FENDERS INTERNATIONAL, INC.



- Ultra heavy-duty central steel core load distribution construction
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam



- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam
- Thick, tough filament nylon tire cord reinforced urethane skin

Ocean Guard™ Cylindrical Buoys

Buoy Model	Buoyancy, Net		Diameter		Length		Height Overall		Buoy Weight		Working Load	
	lb.	kg	ft.	m.	ft.	m	ft.	m.	lb.	kg.	lb.	tons
CB-5	110	50	1.20	0.37	2.1	0.64	6.12	1.87	82	37	5,000	2,268
CB-10	221	100	1.47	0.45	2.6	0.78	6.93	2.11	105	48	5,000	2,268
CB-15	331	150	1.65	0.50	2.9	0.88	7.64	2.33	125	57	5,000	2,268
CB-25	551	250	1.94	0.59	3.4	1.03	8.62	2.63	161	73	7,500	3,401
CB-45	992	450	2.34	0.71	4.1	1.25	9.24	2.81	246	112	10,000	4,535
CB-70	1,544	700	2.70	0.82	4.7	1.44	9.90	3.02	355	161	10,000	4,535
CB-100	2,205	1,000	3.02	0.92	5.3	1.61	10.38	3.16	436	198	20,000	9,070
CB-115	2,536	1,150	3.18	0.97	5.6	1.70	10.90	3.32	562	255	20,000	9,070
CB-140	3,087	1,400	3.39	1.03	5.9	1.81	11.36	3.46	626	284	20,000	9,070
CB-180	3,969	1,800	3.69	1.12	6.5	1.97	12.03	3.67	839	380	40,000	18,141
CB-230	5,072	2,300	3.99	1.22	7.0	2.13	12.41	3.78	960	435	40,000	18,141
CB-275	6,064	2,750	4.22	1.29	7.4	2.25	12.76	3.89	1,065	483	40,000	18,141

* Actual values for above sizes may vary +/- 15% due to variations in materials,, temperatures and tolerances.

Marine Fenders International, Inc.

• 909 Mahar Avenue • Wilmington • California • 90744 • USA

Telephone 1-310-834-7037 • Fax 1-310-834-7825 • E-mail: sales@marinefendersintl.com • www.marinefendersintl.com