



# MARINE FENDERS INTERNATIONAL, INC.



- Ultra heavy-duty central steel core load distribution construction.
- US Coast Guard approved inner closed cell rigid urethane buoyancy foam.



- Impact absorbing, resilient heat laminated cross-linked polyethylene foam core foam.
- Thick, tough filament nylon tire cord reinforced urethane skin.

## Ocean Guard™ Mooring Buoys T-Top

Buoy Model MB #	Buoyancy, Net		Diameter		Height		Height Overall		Buoy Weight		Working Load		Shackle Size (Typ.)	
	lb.	kg	ft.	m.	ft.	m	ft.	m.	lb.	kg.	lb.	tons	in.	mm.
MB-25-TT	5,512	2,500	6.19	1.89	3.64	1.11	6.12	1.87	1,548	702	100,000	45	1.75	44
MB-35-TT	7,716	3,500	6.92	2.11	4.07	1.24	6.93	2.11	2,112	958	150,000	68	2.0	51
MB-50-TT	11,023	5,000	7.73	2.35	4.55	1.39	7.64	2.33	2,652	1,203	150,000	68	2.0	51
MB-70-TT	15,432	7,000	8.63	2.63	5.08	1.55	8.62	2.63	3,609	1,637	200,000	91	2.5	64
MB-90-TT	19,842	9,000	9.33	2.84	5.49	1.67	9.24	2.81	4,246	1,926	200,000	91	2.5	64
MB-115-TT	25,353	11,500	10.08	3.07	5.93	1.81	9.90	3.02	5,008	2,271	200,000	91	2.5	64
MB-135-TT	29,762	13,500	10.63	3.24	6.25	1.91	10.38	3.16	5,856	2,656	300,000	136	3.0	76
MB-160-TT	35,274	16,000	11.21	3.42	6.60	2.01	10.90	3.32	6,569	2,979	300,000	136	3.0	76
MB-185-TT	40,785	18,500	11.74	3.58	6.91	2.11	11.36	3.46	7,262	3,293	300,000	136	3.0	76
MB-225-TT	49,604	22,500	12.50	3.81	7.35	2.24	12.03	3.67	8,344	3,784	300,000	136	3.0	76
MB-250-TT	55,116	25,000	12.93	3.94	7.60	2.32	12.41	3.78	9,001	4,082	300,000	136	3.0	76
MB-275-TT	60,627	27,500	13.33	4.06	7.84	2.39	12.76	3.89	9,650	4,376	300,000	136	3.0	76
MB-340-TT	74,957	34,000	14.27	4.35	8.39	2.56	13.59	4.14	11,297	5,123	300,000	136	3.0	76
MB-455-TT	100,310	45,500	14.50	4.42	10.74	3.27	17.11	5.21	13,570	6,154	300,000	136	3.0	76

\* Actual values for above sizes may vary +/- 15% due to variations in materials, temperatures and tolerances.

### Marine Fenders International, Inc.

• 909 Mahar Avenue • Wilmington • California • 90744 • USA

Telephone 1-310-834-7037 • Fax 1-310-834-7825 • E-mail: sales@marinefendersintl.com • www.marinefendersintl.com